

MS120 Switches

Layer 2 access switches with 1G SFP uplinks,
designed for small branch deployments



Cloud managed access switches

Cisco Meraki **MS120** switches provide Layer 2 access switching ideal for branch and campus deployments. The MS120 series features a variety of power options designed to meet the diverse needs of large enterprise networks.

Cisco Meraki switches are built from the ground up for cloud management without compromising any of the power and flexibility traditionally found in enterprise-class switches.

All Cisco Meraki switches are managed through an elegant, intuitive cloud interface, rather than a cryptic command line.

To bring up a Meraki switch, simply plug it in. Meraki switches do not require CLI for switch configuration or port management.

Meraki's centralized management platform gives administrators granular visibility into their network. Our dashboard helps you keep track of every configuration change in your network with our detailed event and change logs.

Industry-leading cloud management

Cloud management has a number of benefits that make it easier to build networks large and small:

- Automatic email alerts from power loss, downtime, excessive Layer 1 errors, or configuration changes
- Powerful remote diagnostic tools such as packet capture to help isolate and troubleshoot network issues
- Role-based administration
- Firmware upgrades and enhancements from the Meraki cloud
- Virtual Stacking enables switch port configuration changes on the dashboard interface without the need to physically stack switches
- Incredible network transparency with application, operating system, client, and hostname visibility
- Zero-touch provisioning for rapid deployment across sites

Product highlights

- Gigabit access switching with 24- and 48- port models and PoE+ support
- Up to 740 watt PoE budget with PoE+ support and dynamic power allocation for powering APs, phones, cameras, and other PoE-enabled devices
- 4 x 1G SFP uplink interfaces on all models
- Non-blocking switch with up to 104 Gbps bandwidth support
- Fanless design on select models
- Lifetime hardware warranty and advanced replacement at no additional cost
- 6 configurable QoS queues for converged voice, video, and data applications
- Low power consumption, quiet acoustic design, and shallow rack depth options, enabling flexible deployment in wiring closets as well as offices and classrooms

Features & capabilities

Meraki switches include all of the traditional Ethernet features found in modern enterprise access switches, including:

Branch & campus access

PoE and PoE+ models available for device level powering
Quality-of-Service (QoS) to prioritize mission critical traffic such as voice and video
Voice VLAN support for simplified VoIP deployments
CDP/LLDP with detailed neighbor discovery and visibility
Port Mirroring support for monitoring network traffic at line rate
IGMP Snooping to optimize network performance for multicast applications
Link Aggregation Control Protocol (LACP) for high-capacity trunking

Network security

IEEE 802.1X, MAB, and Hybrid authentication support for wired access control with RADIUS server monitoring
ACL support (IPv4 & IPv6) and MAC whitelisting
Single-Host/Multi-Domain/Multi-Host/Multi Authentication
Change of Authorization (CoA) and RADIUS accounting support
DHCP snooping to prevent users from adding unauthorized DHCP servers on the network
Rapid spanning tree, BPDU guard, root guard, loop guard, UDLD and other safeguards to help prevent misconfigurations and reduce convergence time
Per-port VLAN configuration
Multiple administrative roles with sophisticated security policy management

Network troubleshooting & automation

Virtual Stacking helps IT admins make configuration changes to hundreds of switch ports in seconds with our intuitive dashboard interface
Configuration templates for rapid, zero-touch provisioning and auditing of all sites
Network Topology for automatic and interactive network mapping
Remote cable testing, packet capture and client discovery
Automatic and scheduled firmware upgrades for the complete network

Converged voice, video and data environments

The Meraki switch family is designed to unify data, voice, and video onto a single IP backbone. All Meraki switches support rich quality-of-service (QoS) functionality for prioritizing data, voice, and video traffic. The switches support eight class-of-service (CoS) queues on every port, enabling them to maintain end-to-end traffic prioritization.

PoE models provide power to VoIP telephones, IP security cameras, wireless access points (APs), and other IP devices. In addition, using CDP and LLDP, PoE power is intelligently budgeted to maximize the number of PoE clients supported.

Application layer visibility

Meraki switches include integrated Layer 7 fingerprinting without the need to purchase additional modules or services. Identify hundreds of applications from business apps to BitTorrent and YouTube.


User fingerprinting allows administrators to quickly identify individual users by device and tune network resources for optimum performance.

Unified software architecture

Meraki switches run the same operating system used by all of our products, which allows us to deliver a consistent user experience for network management.

When connected, new MS120 switches automatically reach out to the Meraki cloud and download the most current configuration. Future updates can be user-scheduled, ensuring the network is kept up-to-date with bug fixes, security updates, and new features.

Virtual stacking with Meraki



The screenshot shows a web interface for configuring switch ports. At the top, it says "Switch ports" and "for the last day". Below that are buttons for "Edit", "Aggregate", "Split", "Mirror", and "Unmirror", along with a search box containing "switch:Closet 1.1.2". The main content is a table with columns for "Switch / Port", "Switch", "Type", and "VLAN".

Switch / Port	Switch	Type	VLAN
<input type="checkbox"/> Closet 1.1.2 / 1	Closet 1.1.2	trunk	native 128
<input type="checkbox"/> Closet 1.1.2 / 2	Closet 1.1.2	trunk	native 128
<input type="checkbox"/> Closet 1.1.2 / 3	Closet 1.1.2	trunk	native 128

Simplified management & operations


Meraki's cloud-managed architecture makes it simpler than ever to quickly provision and reconfigure switch ports with security, QoS, and other parameters. The Meraki dashboard provides unified policies, event logs, and monitoring, which make it easy to manage and grow scale network deployments.

By providing a complete, powerful set of management functions over the cloud, Meraki cloud-based management eliminates the need


for proprietary command line configuration interfaces which require expensive and time-consuming certifications. Meraki MS switches can be fully deployed and provisioned in minutes, without requiring any local configuration or staging. Additional or replacement switches can be sent to remote offices and installed by non-technical staff, saving thousands of dollars in time and travel expenses.

The Meraki MS family also includes several remote diagnostic features, from network connectivity and cable integrity tests to latency measurement tools. For deep client troubleshooting, administrators can even perform per-port remote pcap packet captures without any additional probes or hardware on-site.

Staged, scheduled, and automatic firmware updates



Automatic email alerts



Enabled security alerts	Security policy	On failing compliance	On entering compliance	Grace period	Scope
<input type="checkbox"/>	Encrypted	<input type="checkbox"/>	<input type="checkbox"/>	15 minutes	with ANY of the following tags
<input type="checkbox"/>	MerakiSecure	<input type="checkbox"/>	<input type="checkbox"/>	30 minutes	All devices

Designed for reliability & environmental efficiency

The Meraki switch family was designed for reliable operation in network closet environments, which may be prone to high temperatures and limited ventilation. By minimizing total component count and only using proven switching silicon, Meraki is able to deliver highly reliable products with exceptional mean time between failure (MTBF) ratings.

Each Meraki switch also operates with a split-plane architecture, where silicon-based switching and data forwarding are separated from software-based control and management. By decoupling the underlying switching logic from control, each unit is able to deliver wire-speed switching even when advanced software features such as Layer 7 host and OS fingerprinting are enabled.

Finally, the highly integrated designs of Meraki switches result in power and cooling savings in large deployment environments of 30-60% when compared with similar managed Gigabit switches.

Distributed branches & remote sites

Meraki's cloud-based system makes it easy to manage a single switch, or thousands of distributed switches, from a single interface.

- Troubleshoot problems remotely; e.g., find which port has a bad cable attached.
- Add or replace switches without having to send a technician on-site. Switches automatically download their current configuration as soon as they are connected to the network.
- Receive email alerts or SMS messages whenever there's a problem at a remote site.

Campus edge

- MS switches are ideal for small and large scale campus deployments, where reliability, scalability, and manageability are top priorities.
- Virtual Stacking helps IT admins control port access policies, apply VLANs, toggle port power and more.
- 1GbE cable SFP ports with link aggregation provide long range connectivity to aggregation switches such as the MS410.
- Get alerts if any switch fails or goes offline, before users complain.

Dimensions & interfaces

Model	Physical dimensions (H x W x D)*	Weight	Interface	Switching capacity
MS120-24-HW	1.73 x 17.32 x 9.84" (4.40 x 44 x 25cm)	8.09 lb (3.67 kg)	<ul style="list-style-type: none"> • 24 x 10/100/1000BASE-T Ethernet RJ45 with auto negotiation and crossover detection (auto-MDIX crossover) • 4 x 1G SFP uplink • RJ45 Management port 	56 Gbps
MS120-24P-HW	1.73 x 17.32 x 9.84" (4.40 x 44 x 25cm)	9.26 lb (4.20 kg)	<ul style="list-style-type: none"> • 24 x 10/100/1000BASE-T Ethernet RJ45 with auto negotiation and crossover detection (auto-MDIX crossover) • 4 x 1G SFP uplink • RJ45 Management port 	56 Gbps
MS120-48-HW	1.73 x 17.32 x 9.84" (4.40 x 44 x 25cm)	8.97 lb (4.06 kg)	<ul style="list-style-type: none"> • 48 x 10/100/1000BASE-T Ethernet RJ45 with auto negotiation and crossover detection (auto-MDIX crossover) • 4 x 1G SFP uplink • RJ45 Management port 	104 Gbps
MS120-48LP-HW	1.73" x 17.32" x 13.39" (4.40 x 44 x 34cm)	12.70 lb (5.70 kg)	<ul style="list-style-type: none"> • 48 x 10/100/1000BASE-T Ethernet RJ45 with auto negotiation and crossover detection (auto-MDIX crossover) • 4 x 1G SFP uplink • RJ45 Management port 	104 Gbps
MS120-48FP-HW	1.73" x 17.32" x 13.39" (4.40 x 44 x 34cm)	12.70 lb (5.70 kg)	<ul style="list-style-type: none"> • 48 x 10/100/1000BASE-T Ethernet RJ45 with auto negotiation and crossover detection (auto-MDIX crossover) • 4 x 1G SFP uplink • RJ45 Management port 	104 Gbps

*Depth includes all accessories

Power options & specifications

Model	Idle / Full load power	Available PoE/PoE+ power	Power supply configuration
MS120-24-HW	8 / 18 W	–	Fixed internal
MS120-24P-HW	28 / 425 W	370 W	Fixed internal
MS120-48-HW	17 / 36 W	–	Fixed internal
MS120-48LP-HW	37 / 478 W	370 W	Fixed internal
MS120-48FP-HW	37 / 908 W	740 W	Fixed internal

What's included

All models

1 x Rack mounting screw kit



The MA-PWR-CORD is included only in units ordered in North America.

The Meraki MS family also supports SFP pluggable optics for high-speed connectivity.

Full specifications and compatibility information is available in the [Meraki Accessories datasheet](#).

MS120 specifications

Management

Managed via the Web with the Meraki cloud management platform

Integrated with Meraki Wireless and complete portfolio of IT products and solutions

Zero-touch remote provisioning (no staging needed)

Detailed historical per-port and per-client usage statistics

Operating System, device, and hostname fingerprinting

SNMP and SYSLOG support for integration with other network management solutions

Automatic firmware upgrades with scheduling control

Remote diagnostics

Email, SMS and mobile push notification alerts¹

Ping, traceroute, cable testing, and link failure detection with alerting
Remote packet capture

Dynamic and interactive network discovery and topology

Combined event and configuration change logs with instant search

Stacking

Virtual Stacking supports thousands of switch ports in a single logical stack for unified management, monitoring, and configuration

Performance

Switching capacity: 56Gbps on 24-port models, 104Gbps on 48-port models

Forwarding rate: 41.67mpps on 24-port models, 77.38 mpps on 48-port models

Jumbo frame (9578 byte Ethernet frame)

Flow control

Ethernet switching capabilities

802.1p Quality of Service, 8 queues (w/ 6 configurable for DSCP-to-CoS mapping)

802.1Q VLAN and trunking support for up to 4,094 VLANs

802.1w, 802.1D Rapid Spanning Tree Protocol (RSTP, STP)

802.1ab Link Layer Discovery Protocol (LLDP) and Cisco Discovery Protocol (CDP)

802.3ad Link aggregation with up to 8 ports per aggregate

Port mirroring

IGMP snooping for multicast filtering

MAC forwarding entries: 16K on 24-port models, 32K on 48-port models

Power

Power input: 100 - 240 VAC, 47-63 Hz

Power consumption: 8 - 908W

Mounting

1U Rack-mountable with included rack mount hardware

2-post front mounting options available

Desktop-mountable with included feet

Environment

Operating temperature: 0 °C to 45 °C

Humidity: 5 to 95% non-condensing

MS120-24, MS120-48 feature fanless operation

¹ Requires carrier-supported email to SMS gateway and/or Meraki Mobile app

MS120 specifications

Security

Integrated multi-factor authentication for Dashboard management

Role-based access control (RBAC) with granular device and configuration control

Corporate wide password policy enforcement

IEEE 802.1X RADIUS and MAB, hybrid authentication and RADIUS server testing

Single-Host/Multi-Domain/Multi-Host/Multi Authentication

Port security: Sticky MAC, MAC whitelisting

DHCP snooping, detection and blocking

IPv4 and IPv6 ACLs

Regulatory²

CSA-US (US, Canada) FCC (USA)

FCC (USA)

IC (Canada)

CE (Europe)

RCM (Australia/New Zealand)

RoHS

² For international availability, please contact sales@meraki.com

Warranty

Full lifetime hardware warranty with next-day advanced replacement included

MTBF ratings (in hours)

Model	MTBF (at 25c)
MS120-24-HW	707,873
MS120-24P-HW	453,906
MS120-48-HW	692,887
MS120-48LP-HW	438,920
MS120-48FP-HW	660,538