

UniFi[®] Network



UniFi LTE Pro

Third-Party SIM Card Support.

Avoid internet downtime and lost productivity by adding a UniFi LTE Pro to your existing UniFi network.

UniFi LTE Pro provides backup cellular internet connectivity to ensure your UniFi WAN network is always running. This model works in the EU region and supports European LTE and WCDMA bands. It has a Nano SIM card slot for your own card. Insert the Nano SIM, connect to any switch port in your corporate network, and activate the device.



Mechanical

Dimensions 66 x 202 x 32 mm (2.60 x 7.96 x 1.27")

Weight Without Stand: 223 g (7.86 oz)
With Stand: 336 g (11.85 oz)

Enclosure Material Polycarbonate

Mount Materials Stand: Aluminum
Wall Mount: Polycarbonate

Hardware

Processor 74 Kc MIPS Processor at 775 MHz

Memory Information 128 MB DDR2

Management Interface Ethernet

Networking Interfaces (2) 10/100/1000 Mbps RJ45 Port
WP7607 LTE

SIM Nano-SIM

LTE Bands CAT4, B1/3/7/8/20/28

LCM Display 1.54" Screen

Power Method 802.3at PoE, Passive PoE (48V)

Power Supply 802.3at PoE (Pins 1, 2+/3, 6- or 4, 5+/7, 8-)

Supported Voltage Range 44 to 57VDC

Max. Power Consumption 8.5W

Max. TX Power 19 dBm

MIMO U-LTE 2 x 2 Category 4 LTE Radio

Throughput Speeds 150 Mbps

Antenna Gain	LTE	B1	2 dBi
		B3	1.5 dBi
		B7	2 dBi
		B8	3.5 dBi
		B20	2 dBi
		B28	2 dBi

Button Factory Reset

Mounting Wall Mount/Foot Stand (Included)

ESD/EMP Protection Air/Contact: ± 24 kV

Operating Temperature -10 to 60° C (-14 to 140° F)



Operating Humidity	5 to 95% Noncondensing
Certifications	CE, FCC, IC



Specifications are subject to change. Ubiquiti products are sold with a limited warranty described at www.ui.com/support/warranty

©2020 Ubiquiti Inc. All rights reserved. Ubiquiti, Ubiquiti Networks, the Ubiquiti U logo, the Ubiquiti beam logo, UniFi, and UniFi Network are trademarks or registered trademarks of Ubiquiti Inc. in the United States and in other countries. All other trademarks are the property of their respective owners.